



The 2015 IECC was adopted with amendments in Utah and went into effect on **July 1, 2019**. This document summarizes changes to the building envelope-related requirements in the updated code for Utah.



CODE CHANGE HIGHLIGHTS

- Utah added a compliance path option to R401.2 that uses REScheck 2012 Utah Energy Conservation code. It requires showing a better performing building and increases in baseline stringency over time.
- Added a phased-in approach to reduce air leakage down to 3 ACH50 by January 1, 2021.
- Utah has implemented a phased-in approach to post-construction duct testing to reduce its target number to 6 CFM25/ 100 sq ft. by January 1, 2021.

BUILDING ENVELOPE REQUIREMENTS

CODE PATH	2015 IECC CODE SECTION	CHANGE SUMMARY		
		CLIMATE ZONE 3	CLIMATE ZONE 5	CLIMATE ZONE 6
Prescriptive	R402.1.2 – Wood Frame Wall	R-20 or R-13 + 5 ci / U-0.060	R-20 or R-13 + 5 ci / U-0.060	R-20 + 5 ci or R-13 + 10 ci / U-0.045
	R402.1.2 – Ceilings	R-38 / U-0.030	R-49 / U-0.026	R-49 / U-0.026
	R402.1.2 – Basement	R-13 or R-5 ci / U-0.091	R-19 or R-15 ci / U-0.050	R-19 or R-15 ci / U-0.050
	R402.1.2 – Crawl Space Walls	R-13 or R-5 ci / U-0.0136	R-19 or R-15 ci / U-0.055	R-19 or R-15 ci / U-0.055
	R402.1.2 – Fenestration	U-0.035	U-0.32	U-0.32

DUCT LEAKAGE

MEASUREMENT	CFM25 / 100 SQ. FT.
Rough-in (installed air handler)	8
Rough-in (air handler not installed)	6
Post-construction (beginning Jan. 1, 2017)	8
Post-construction (beginning Jan. 1, 2019)	7
Post-construction (beginning Jan. 1, 2021)	6

AIR LEAKAGE

CLIMATE ZONES 5 & 6	MEASUREMENT
January 1, 2019	3.5 ACH50
Beginning January 1, 2021	3 ACH50

TABLE R406.4 MAXIMUM ENERGY RATING INDEX (ERI)

CLIMATE ZONE	MAXIMUM ERI
3	65
5	69
6	68

Note: All R-values are minimums and U-factors maximums.

MORE INFORMATION ON THE UTAH ENERGY CODE CAN BE FOUND HERE:

https://utahenergycode.com/wp-content/uploads/2015-IECC-UtahCom_ResAmendments-041516.pdf




ENERGY-EFFICIENT, COST-EFFECTIVE CONSTRUCTION WITH FIBERGLASS AND MINERAL WOOL INSULATION



As code levels advance, **keep informed about innovative practices** to meet or exceed code requirements using cost-effective fiberglass and mineral wool insulation.

The following resources in the table below are just a subset of the many guides available from the **Insulation Institute** to help you achieve new performance requirements with proven approaches.


INSULATION INSTITUTE RESOURCES



Air Leakage

As states adopt more stringent energy codes, some builders may experience challenges meeting new mandatory air leakage requirements. Fiberglass and mineral wool insulation is the low-cost solution for homebuilders to meet or surpass code air leakage rate requirements of 3 or 5 air changes per hour depending on climate zone. For homeowners, an airtight building envelope results in energy savings and increased thermal comfort.

<https://insulationinstitute.org/wp-content/uploads/2018/05/N090-5-Air-Sealing-Locations-for-New-Homes.pdf>



Ducts Buried Within Ceiling Insulation

Deeply buried ducts in attics is an easy way to lower energy code compliance costs for builders using the simulated energy performance path. Homeowners can benefit from energy savings realized from lower-capacity, lower-cost HVAC systems.


<https://insulationinstitute.org/wp-content/uploads/2019/03/N087-Buried-Ducts-The-newest-way-to-uncover-savings.pdf>



Proper Installation of Insulation

Grade I installation delivers superior energy efficiency and is increasingly required by state energy codes. Insulation installation jobs that fail to meet Grade I criteria can mean construction delays due to callbacks, HERS rating penalties, and failed code inspections. Grade I installation is readily achievable by following basic guidelines as recommended by manufacturers. NAIMA offers free online training for installers.

www.grade1insulation.org



Unvented Attics Using Fiberglass and Mineral Wool Insulation

Unvented attics can be constructed by installing fiberglass or mineral wool insulation below the roof deck instead of using more costly materials like spray foam. In addition, fiberglass and mineral wool insulation products are green certified and do not carry recommended occupancy restrictions due to product off-gassing after installation. Starting with the 2018 IRC, this practice is outlined in detail within the code. Homeowners benefit from lower construction costs and the use of a safe product.

<https://insulationinstitute.org/wp-content/uploads/2018/05/BuildingUnventedAtticAssemblies-N089.pdf>

LEARN MORE ABOUT THE ERI COMPLIANCE PATH HERE:

www.energycodes.gov/resource-center/training-courses/2015-iecc-%E2%80%93-energy-rating-index-eri-compliance-alternative

Get the Facts for a Stronger Business

Learn more about fiberglass and mineral wool insulation at InsulationInstitute.org



P.O. Box 1906 • Alexandria, VA 22313
InsulationInstitute.org • 703.684.0084