2022SUMMARY OF KEYCONNECTICUTRESIDENTIAL ENERGYSTATE BUILDING CODECODE REQUIREMENTS

The 2021 IECC with Connecticut specific amendments went into effect on **October 1, 2022**. This document summarizes changes to the building envelope-related requirements in the updated code for Connecticut.

CODE CHANGE HIGHLIGHTS

- Foamed-in-place insulating material, except urethane foam insulation or styrene foam insulation, shall not be sold or installed in the state on or after May 28, 2013, unless the manufacturer or supplier has certified to the State Building Inspector that the materials comply with the provision of section 29-277 of the Connecticut General Statutes.
- ERI-based compliance per R406.5 shall be demonstrated without the use of on-site renewable energy.
- R401.2.5 Additional Energy Efficiency is not required when using the ERI path.
- Insulation levels increased in walls and ceilings.



BUILDING ENVELOPE AND DUCT REQUIREMENTS

CODE PATH 2		021 IECC CODE SECTION		CHANGE SUMMARY		
GUDE PAIN	2021 TEGG GODE SECTION			CLIMATE ZONE 5		
	R402.1.2 – Wood Frame Wall			R-30 or R-20+5 ci or R13+10 ci or R-20 ci / U-0.045		
Prescriptive	R402.1.2 – Ceilings			R-60 / U-0.024		
	R402.1.2 – Basement Walls			R-19 or R-15 ci or R-13+5 ci / U-0.050		
	R402.1.2 – Crawl Space Walls			R-19 or R-15 ci or R-13+5 ci / U-0.055		
	R402.1.2 – Fenestration			U-0.30		
DUCT LEAKAGE			DUCT R-	-VALUE AIR LEAKAGE		EAKAGE
MEASUREMENT		CFM25 / 100 SQ. FT.	R-VALUE		CLIMATE ZONE	MEASUREMENT
Rough-in (installed air handler)		4				
Rough-in (air handler not installed)		3	R-8 ª		5	3 ACH50
Post-construction		4				

TABLE R406.4 MAXIMUM ENERGY RATING INDEX (ERI)

CLIMATE ZONE

5

MAXIMUM ERI

55

a. R-6 is allowed for ducts <3 inches.

ACCESS THE FULL CONNECTICUT STATE BUILDING CODE AMENDMENTS HERE:

https://codes.iccsafe.org/content/IECC2021P2

Insulation Institute

This summary is offered for informational purposes only. It does not purport to be an exhaustive analysis of code changes or provide advice that will ensure guaranteed compliance with any energy code provision. Please consult with local authorities before finalizing your installation plans.

ENERGY-EFFICIENT, COST-EFFECTIVE CONSTRUCTION WITH FIBERGLASS AND MINERAL WOOL INSULATION



As code levels advance, **keep informed about innovative practices** to meet or exceed code requirements using cost-effective fiberglass and mineral wool insulation.

The following resources in the table below are just a subset of the many guides available from the **Insulation Institute** to help you achieve new performance requirements with proven approaches.

INSULATION INSTITUTE RESOURCES

5 Priority Air Sealing Locations for New Homes	Air Leakage	As states adopt more stringent energy codes, some builders may experience challenges meeting new mandatory air leakage requirements. Fiberglass and mineral wool insulation is the low-cost solution for homebuilders to meet or surpass code air leakage rate requirements of 3 or 5 air changes per hour depending on climate zone. For homeowners an airtight building envelope results in energy savings and increased thermal comfort. https://insulationinstitute.org/wp-content/uploads/2018/05/N090-5-Air-Sealing-
investigation legilitate.		Locations-for-New-Homes.pdf
	Ducts Buried Within Ceiling Insulation	Deeply buried ducts in attics is an easy way to lower energy code compliance costs for builders using the simulated energy performance path. Homeowners can benefit from energy savings realized from lower-capacity, lower-cost HVAC systems.
		https://insulationinstitute.org/wp-content/uploads/2019/03/N087-Buried-Ducts-The- newest-way-to-uncover-savings.pdf
	Proper Installation of Insulation	Grade I installation delivers superior energy efficiency and is increasingly required by state energy codes. Insulation installation jobs that fail to meet Grade I criteria can mean construction delays due to callbacks, HERS rating penalties, and failed code inspections. Grade I installation is readily achievable by following basic guidelines as recommended by manufacturers. NAIMA offers free online training for installers. www.grade1insulation.org
	Unvented Attics Using Fiberglass and Mineral Wool Insulation	Unvented attics can be constructed by installing fiberglass or mineral wool insulation below the roof deck instead of using more costly materials like spray foam. In addition, fiberglass and mineral wool insulation products are green certified and do not carry recommended occupancy restrictions due to product off-gassing after installation. Starting with the 2018 IRC, this practice is outlined in detail within the code. Homeowners benefit from lower construction costs and the use of a safe product. https://insulationinstitute.org/wp-content/uploads/2018/05/ BuildingUnventedAtticAssemblies-N089.pdf
	LEARN MOR	BuildingUnventedAtticAssemblies-N089.pdf

https://www.energycodes.gov/technical-assistance/training/courses/ 2015-iecc-energy-rating-index-eri-compliance-alternative

Get the Facts for a Stronger Business

Learn more about fiberglass and mineral wool insulation at InsulationInstitute.org

NAIMA NORTH AMERICAN INSULATION

2013 Olde Regent Way • Suite 150, Box 120 • Leland, NC 28451 InsulationInstitute.org • 703.684.0084