

The 2018 IECC was adopted with Hawaii specific amendments on **December 15, 2022**. This document summarizes changes to the building envelope-related requirements in the updated code for Hawaii.



CODE CHANGE HIGHLIGHTS

- Three envelope compliance options are available: Standard, Tropical and Points-based.
 - o Residential buildings using the standard option must meet the requirements of the table below.
 - o Residential buildings in tropical zones that are constructed at elevations below 2,400 feet must meet certain criteria, including installing R-19 or greater insulation or the cool roof requirements in Section C402.3 in ceilings under Section R401.2.1.
 - o The points-based option allows the use of one or more efficiency measures for roof and above-grade wall systems from Table R407.1 that cumulatively equal or exceed 0 points.
- Solar water heaters are required for new single-family residential construction.

BUILDING ENVELOPE AND DUCT REQUIREMENTS

CODE PATH	2018 IECC CODE SECTION	CHANGE SUMMARY
		CLIMATE ZONE 1
Prescriptive	R402.1.2 – Wood Frame Wall	R-13
	R402.1.2 – Ceilings	R-30
	R402.1.2 – Slab	N/A
	R402.1.2 – Crawl Space Walls	N/A
	R402.1.2 – Fenestration	SHGC 0.25

DUCT LEAKAGE		DUCT R-VALUE		AIR LEAKAGE	
MEASUREMENT	CFM25 / 100 SQ. FT.	R-VALUE	CLIMATE ZONE	MEASUREMENT	
Rough-in (installed air handler)	4	R-8 ^a	1	3 ACH50	
Rough-in (air handler not installed)	3				
Post-construction	4				

TABLE R406.4 MAXIMUM ENERGY RATING INDEX (ERI)

CLIMATE ZONE	MAXIMUM ERI
1	57

a. In attics. R-6 in other portions of the building. R-6 and R-4.2 respectively for ducts <3 inches.

MORE INFORMATION ON THE HAWAII BUILDING CODE CAN BE FOUND HERE:

https://energy.hawaii.gov/wp-content/uploads/2022/06/soh_bcc_energycode_20201215.pdf



ENERGY-EFFICIENT, COST-EFFECTIVE CONSTRUCTION WITH FIBERGLASS AND MINERAL WOOL INSULATION



As code levels advance, **keep informed about innovative practices** to meet or exceed code requirements using cost-effective fiberglass and mineral wool insulation.

The following resources in the table below are just a subset of the many guides available from the **Insulation Institute** to help you achieve new performance requirements with proven approaches.


INSULATION INSTITUTE RESOURCES



Air Leakage

As states adopt more stringent energy codes, some builders may experience challenges meeting new mandatory air leakage requirements. Fiberglass and mineral wool insulation is the low-cost solution for homebuilders to meet or surpass code air leakage rate requirements of 3 or 5 air changes per hour depending on climate zone. For homeowners, an airtight building envelope results in energy savings and increased thermal comfort.

<https://insulationinstitute.org/wp-content/uploads/2018/05/N090-5-Air-Sealing-Locations-for-New-Homes.pdf>



Ducts Buried Within Ceiling Insulation

Deeply buried ducts in attics is an easy way to lower energy code compliance costs for builders using the simulated energy performance path. Homeowners can benefit from energy savings realized from lower-capacity, lower-cost HVAC systems.

<https://insulationinstitute.org/wp-content/uploads/2019/03/N087-Buried-Ducts-The-newest-way-to-uncover-savings.pdf>



Proper Installation of Insulation

Grade I installation delivers superior energy efficiency and is increasingly required by state energy codes. Insulation installation jobs that fail to meet Grade I criteria can mean construction delays due to callbacks, HERS rating penalties, and failed code inspections. Grade I installation is readily achievable by following basic guidelines as recommended by manufacturers. NAIMA offers free online training for installers.

www.grade1insulation.org



Unvented Attics Using Fiberglass and Mineral Wool Insulation

Unvented attics can be constructed by installing fiberglass or mineral wool insulation below the roof deck instead of using more costly materials like spray foam. In addition, fiberglass and mineral wool insulation products are green certified and do not carry recommended occupancy restrictions due to product off-gassing after installation. Starting with the 2018 IRC, this practice is outlined in detail within the code. Homeowners benefit from lower construction costs and the use of a safe product.

<https://insulationinstitute.org/wp-content/uploads/2018/05/BuildingUnventedAtticAssemblies-N089.pdf>

LEARN MORE ABOUT THE ERI COMPLIANCE PATH HERE:

<https://www.energycodes.gov/technical-assistance/training/courses/2015-iecc-energy-rating-index-eri-compliance-alternative>

Get the Facts for a Stronger Business

Learn more about fiberglass and mineral wool insulation at InsulationInstitute.org



2013 Olde Regent Way • Suite 150, Box 120 • Leland, NC 28451
InsulationInstitute.org • 703.684.0084