## MONTANA Energy Code

## SUMMARY OF KEY RESIDENTIAL ENERGY CODE REQUIREMENTS

The 2021 IECC was adopted with amendments in Montana effective **June 20, 2022**. This document summarizes changes to the building envelope-related requirements in the updated code for Montana.

## **CODE CHANGE HIGHLIGHTS**

- Mechanical system piping, service hot water system insulation and hot water pipe insulation requirements were amended to align with the Uniform Plumbing Code (UPC) requirements.
- The ceiling U-factor in Table R402.1.2 was amended to U-0.026 but the minimum ceiling R-value in Table R 402.1.3 was left unamended at R-60.
- The Montana Department of Labor and Industry encourages owners, design professionals, and builders to voluntarily implement greater levels of energy efficiency in building design and construction than those required by the International Energy Conservation Code.



#### BUILDING ENVELOPE AND DUCT REQUIREMENTS

PRESCRIPTIVE	CLIMATE ZONE 6		MAXIMUM ENERGY RATING INDEX (ERI)			
Wood Frame Wall	R-21 or R-13+5ci or R-13+10ci or R-15ci / U-0.045		CLIMATE ZONE	MEASUREMENT		
Ceilings		R-60 / U-0.026		6	54	
Crawl Space Walls	R-19 or R-15 ci or R-13+5 ci / U-0.055					
Fenestration	U-0.30		AIR LEAKAGE (IF TESTED)			
Floor	R-30 / U-0.033		CLIMATE ZONE	MEASUREMENT		
Mass Wall <sup>a</sup>	R-15/20 / U-0.060		6	4 ACH50		
Slab R-value	R-10ci / 4 ft.					
Basement Walls	R-19 or	<sup>.</sup> R-15 ci or R-13+5 ci / U-0.050		DUCT R-VALUE		
DUCT LEAKAGE						
MEASUREMENT		CFM25 / 100 SQ. FT.		R-	R-8 <sup>b</sup>	
Rough-in (installed air handler)		4		a. The second R-value/U-factor applies where		
Rough-in (air handler not installed)		3		> 50% of the insulation is on the interior.		
Post-construction		4		b. R-6 is allowed for ducts < 3 inches.		

### MORE INFORMATION ON THE MONTANA ENERGY CODE CAN BE FOUND HERE:

https://bsd.dli.mt.gov/\_docs/building-codes-permits/ProposedRuleAmendments.pdf#page=20



This summary is offered for informational purposes only. It does not purport to be an exhaustive analysis of code changes or provide advice that will ensure guaranteed compliance with any energy code provision. Please consult with local authorities before finalizing your installation plans.

# ENERGY-EFFICIENT, COST-EFFECTIVE CONSTRUCTION WITH FIBERGLASS AND MINERAL WOOL INSULATION



As code levels advance, **keep informed about innovative practices** to meet or exceed code requirements using cost-effective fiberglass and mineral wool insulation.

The following resources in the table below are just a subset of the many guides available from the **Insulation Institute** to help you achieve new performance requirements with proven approaches.

#### **INSULATION INSTITUTE RESOURCES**

<sup>.</sup> Leakage	As states adopt more stringent energy codes, some builders may experience challenges meeting new mandatory air leakage requirements. Fiberglass and mineral wool insulation is the low-cost solution for homebuilders to meet or surpass code air leakage rate requirements of 3 or 5 air changes per hour depending on climate zone. For homeowners, an airtight building envelope results in energy savings and increased thermal comfort. https://insulationinstitute.org/wp-content/uploads/2018/05/N090-5-Air-Sealing-Locations-for-New-Homes.pdf
cts Buried thin Ceiling	Deeply buried ducts in attics is an easy way to lower energy code compliance costs for builders using the simulated energy performance path. Homeowners can benefit from energy savings realized from lower-capacity, lower-cost HVAC systems.
sulation	https://insulationinstitute.org/wp-content/uploads/2019/03/N087-Buried-Ducts-The- newest-way-to-uncover-savings.pdf
oper stallation Insulation	Grade I installation delivers superior energy efficiency and is increasingly required by state energy codes. Insulation installation jobs that fail to meet Grade I criteria can mean construction delays due to callbacks, HERS rating penalties, and failed code inspections. Grade I installation is readily achievable by following basic guidelines as recommended by manufacturers. NAIMA offers free online training for installers. www.grade1insulation.org
vented Attics ing Fiberglass d Mineral ool Insulation	Unvented attics can be constructed by installing fiberglass or mineral wool insulation below the roof deck instead of using more costly materials like spray foam. In addition, fiberglass and mineral wool insulation products are green certified and do not carry recommended occupancy restrictions due to product off-gassing after installation. Starting with the 2018 IRC, this practice is outlined in detail within the code. Homeowners benefit from lower construction costs and the use of a safe product. https://insulationinstitute.org/wp-content/uploads/2018/05/ BuildingUnventedAtticAssemblies-N089.pdf
	ulation per tallation nsulation vented Attics ng Fiberglass I Mineral

https://insulationinstitute.org/wp-content/uploads/2024/10/ Modern-Energy-Codes-Save-Money-Infographic.pdf

#### Get the Facts for a Stronger Business

Learn more about fiberglass and mineral wool insulation at InsulationInstitute.org

NAIMA NORTH AMERICAN INSULATION

2013 Olde Regent Way • Suite 150, Box 120 • Leland, NC 28451 InsulationInstitute.org • 703.684.0084